

Technical Data Sheet

THX _ CATALIZZATORI PER POLIURETANICI _ IT THX _ HARDENERS FOR POLYURETHANES _ EN

November 7, 2025

IT: Le caratteristiche qualitative ed i consigli d'uso sono riportati nelle schede tecniche dei componenti A. I catalizzatori isocianici sono sensibili all'umidità; le confezioni vanno stoccate in ambiente asciutto e devono rimanere ermeticamente chiuse. Quando viene aperta la confezione il prodotto deve essere utilizzato in giornata.

EN: As to other characteristics and method of use, please refer to the technical data sheets relating to part A. Isocyanate hardeners are affected by humidity, therefore packages shall be hermetically sealed and kept dry. Once the package has been opened, the product shall be used up within the same day.

CODE	SHELF-LIFE SCADENZA	SOLID CONTENT RESIDUO SECCO	SPECIFIC GRAVITY PESO SPECIFICO
CODICE	(months)	%	Kg/l
	(mesi)		
THL3073/00	24	27 ± 1	0,930 ± 0,030
THL3109/00	24	40 ± 1	0,985 ± 0,030
THL3163/00	24	35 ± 1	0,980 ± 0,030
THL3256/00	24	38 ± 1	0,970 ± 0,030
THL3348/00	24	28 ± 1	0,950 ± 0,030
THL3354/00	24	50 ± 1	1,001 ± 0,030
THL3355/00	24	19 ± 1	0,893 ± 0,030
THL3364/00	24	24 ± 1	0,940 ± 0,030
THL3445/00	12	36 ± 1	0,985 ± 0,030
THL3491/00	24	38 ± 1	1,004 ± 0,031
THL3508/00	24	32 ± 1	0,967 ± 0,030
THL3555/00	24	29 ± 1	0,981 ± 0,030
THL3616/00	12	36 ± 1	0,992 ± 0,030
THL3625/00	24	23 ± 1	0,960 ± 0,030
THL3626/00	24	19 ± 1	0,893 ± 0,030
THL3627/00	24	36 ± 1	0,950 ± 0,030
THL3651/00	24	25 ± 1	0,934 ± 0,030
THL3752/00	12	22 ± 1	0,930 ± 0,030
THL3753/00	12	21 ± 1	0,930 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

AZIENDA CON
 SISTEMA DI GESTIONE
 - UNI EN ISO 9001 -
 - UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
 Sede Legale ed Amministrativa
 Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
 tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
 Cod. Fisc. e Reg. Impr. Bo 08866930152
 P. IVA: IT 00494251200 - R.E.A. n. 313180
 Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Società soggetta a direzione e coordinamento di The Sherwin-Williams Company, USA

CODE	SHELF-LIFE SCADENZA	SOLID CONTENT RESIDUO SECCO	SPECIFIC GRAVITY PESO SPECIFICO
CODICE	(months) (mesi)	%	Kg/l
THL3825/00	12	21 ± 1	0,940 ± 0,030
THL3850/00	12	30 ± 1	0,970 ± 0,030
THL3852/00	12	24 ± 1	0,960 ± 0,030
THL3896/00	24	100	1,150 ± 0,030
THL7111/00	24	36 ± 1	0,970 ± 0,030
THL7112/00	24	27 ± 1	0,920 ± 0,030
THL7170/00	24	30 ± 1	0,980 ± 0,030
THL7171/00	24	29 ± 1	0,970 ± 0,030
THL7988/00	24	50 ± 1	1,010 ± 0,030
THV6332/00	24	37 ± 1	0,980 ± 0,030
THV7624/00	24	30 ± 1	0,990 ± 0,030
THV7764/00	24	55 ± 1	0,980 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.