




CAR-REP VINYL



**THEORETICAL
COVERAGE**



UV-PROOF



FLEXIBLE



**WEATHER-
PROOF**



SAFETY GEAR




**3 MIN
SHAKE**



**25CM
SPRAY PATTERN**



**5 MIN
TIME BETWEEN LAY-
ERS**



**2 LAYERS
LAYERS**



CLEAN UP



**30 MIN
TOUCH DRY**



**24H
FINAL DRYING**



**VINYL
SOLVENT BASED**

Car-Rep® Vinyl Coat is a flexible coating developed for the restoration and colour renewal of automotive interior surfaces. It is suitable for application on vinyl and leather components such as dashboards, door panels, centre consoles, shifter boots and other interior trim parts.

The product is based on a special formulation containing a maximum adhesion promoter, which enables direct application without the use of a separate primer. After curing, the coating forms a permanent and elastic film with excellent adhesion to the substrate. Under normal interior use, the film will not crack, peel or chip. The paint has fast self-levelling properties and produces a smooth, uniform semi-gloss finish.

At +20 °C and 50 % relative humidity, the coating becomes dust dry after approximately 20 minutes and touch dry after approximately 30 minutes. The surface can be handled after approximately 60 minutes. Final hardness is achieved after approximately 24 hours. Drying and curing times may vary depending on film thickness, temperature and ventilation.

The cured coating has a heat resistance of up to +150 °C.

SIZE: 400ml

SALES QTY:

400ml: 6 pcs

USAGE INSTRUCTIONS:

SURFACE PREPARATION: Clean surface thoroughly. If required, sand with 320 grit sandpaper followed by 400 grit. Then wet sand with 600 or 800 grit. Clean the surface with Degreaser, then wipe with a soft, lint-free cloth. For previously painted surfaces, make sure the previous layer is fully cured before overpainting unless advised otherwise.

APPLICATION: Shake can vigorously for three minutes after agitation ball begins to rattle. Shake often during use. Test the application outside the object or on an inconspicuous area. Hold can upright 25cm from surface, and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion, while spraying same distance from the surface. Apply two light coats to gradually increase film thickness. Application and curing temperature 18-25°C. Allow 5 minutes flash off time between coats. Turn can upside down and spray for 5 seconds to clear nozzle after use.

CLEAN UP: Use Car-Rep Thinner.

CAR-REP Car-Rep Vinyl

Art. No.	CAR-REP Car-Rep Vinyl	Color	Barcode
CR0133009	Spraypaint Car-Rep Vinyl RAL3009 Oxide Red 400ml		6412490028497
CR0139004	Spraypaint Car-Rep Vinyl RAL9004 Signal Black 400ml		6412490028558
CR0131001	Spraypaint Car-Rep Vinyl RAL1001 Beige 400ml		6412490028473
CR0138019	Spraypaint Car-Rep Vinyl RAL8019 Grey brown 400ml		6412490028527
CR0138025	Spraypaint Car-Rep Vinyl RAL8025 Pale brown 400ml		6412490028534
CR0131002	Spraypaint Car-Rep Vinyl RAL1002 Sand yellow 400ml		6412490028480
CR0139003	Spraypaint Car-Rep Vinyl RAL9003 Signal White 400ml		6412490028541
CR0137015	Spraypaint Car-Rep Vinyl RAL7015 Slate Grey 400ml		6412490028510
CR0137000	Spraypaint Car-Rep Vinyl RAL7000 Squirrel Grey 400ml		6412490028503